

More than a simple console, Gaffers Control is *the* essential tool to control all DMX devices in a simple and easy way.



DMX512

CRMX
by LumenRadio

70 W/h



DESCRIPTION AND FUNCTIONS

- ▶ "All-in-one" DMX console in StormCase™ casing
- ▶ 7" capacitive touch screen 800x480 pixels
- ▶ Integrated CRMX LumenRadio™ transmitter
- ▶ Integrated Lithium-ion 70 W/h battery
- ▶ 14 addressable banks/512 DMX addresses
- ▶ Integrated DMX library
Including: Arri, BB&S, Creamsource, Cineo, DMG, Astera, Quasar science, Carpetlight, Litegear, Kino Flo, Litepanels, Dedolight, Alladin, Exalux and more....
- ▶ Update of DMX library via USB
- ▶ Master setting via linear potentiometer
- ▶ Parameter setting via touch screen or buttons
- ▶ DMX outputs on XLR 5Pin
- ▶ Duration of operation on battery: up to 10 hours.



TECHNICAL SPECIFICATIONS

- ▶ Power consumption 15 W
- ▶ Supply voltage: 100-240 VAC 50/60 Hz
- ▶ Type of battery: Li-ion 70 W/h
- ▶ Duration of full charge 5h
- ▶ Range: up to 120 m in an open area depending on the receivers
- ▶ Radio interface: 2.4G hz (2,402-2,480 Ghz)
- ▶ Dimensions: 300 x 249 x 119 mm
- ▶ Weight: 2,725 g



COMPATIBILITY

- ▶ CRMX compatible devices by Lumen Radio™
Lightfixtures with integrated CRMX receiver:
 - Arri S360 - Kino Flo – Litepanels gemini - DMG lumiere MIX
 - Cineo – Litegear – Carpetlight - Creamsource Sky

